

## Declaration of performance

No. CK1 (Valid from 29.06.2017)



1. **Unique identification code of the product type:** Petersen Cover ventilated facade system
2. **Intended use/es:** Ventilated cladding kits comprising cladding components and associated fixings. Petersen Cover cladding kit is intended for use on both new and existing (refurbishment) external walls
3. **Manufacturer:** Petersen Tegl A/S, Nybølnervej 14, DK-6310 Broager
4. **Authorized representative:** Not applicable
5. **System/s of AVPC:** System 2+
6. **European assessment Document:** ETAG 034, April 2012  
**European technical Assesment:** ETA-17/0312, 29/6/2017  
**Technical assesment body/ies:** ETA-Danmark A/S  
**Notified body/ies:** NB 1109
7. **Declared performance/s:**

Essential Characteristics	Performance
Reaction to fire, clay tiles, aluminium and steel components	A1
Reaction to fire, timber	D-s2, d0
Reaction to fire on back side	Please refer to ETA-17/0312 page 4
Watertightness of joints	NPD*
Water permeability and Water vapour permeability	NPD*
Drainability	NPD*
Release of dangerous substances, clay tiles	Tiles does not contain substances mentioned in section 5.3.5.1 of ETAG 034 part 1or of very high concer that are listed by the European Chemicals Agency
Wind load resistance	NPD* (please refer to ETA-17/0312 page 7)
Mechanical resistance, Pull-through resistance of cladding element	Please refer to ETA-17/0312 page 4
Mechanical resistance, Pull-through resistance under shear load	Please refer to ETA-17/0312 page 5
Mechanical resistance, Bending strength	Please refer to ETA-17/0312 page 5
Resistance to horizontal point loads	NPD*
Impact resistance	NPD*
Resistance to seismic actions	NPD*
Sustainable use of natural resources (BR7)	NPD*

\* No performance determined

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Broager, 29.06.2017

  
CFO Poul M. Kjeldsen



**CE**

NB 1109

Petersen Tegl A/S, Nybølnervej 14, DK-6310 Broager

17

Declaration of performance No. CK1 (Valid from 29.06.2017)

ETAG 034, April 2012

ETA-17/0312, 29/6/2017

Ventilated cladding kits comprising cladding components and associated fixings. Petersen Cover cladding kit is intended for use on both new and existing (refurbishment) external walls

Essential Characteristics	Performance
Reaction to fire, clay tiles, aluminium and steel components	A1
Reaction to fire, timber	D-s2, d0
Reaction to fire on back side	Please refer to ETA-17/0312 page 4
Watertightness of joints	NPD*
Water permeability and Water vapour permeability	NPD*
Drainability	NPD*
Release of dangerous substances, clay tiles	Tiles does not contain substances mentioned in section 5.3.5.1 of ETAG 034 part 1 or of very high concern that are listed by the European Chemicals Agency
Wind load resistance	NPD* (please refer to ETA-17/0312 page 7)
Mechanical resistance, Pull-through resistance of cladding element	Please refer to ETA-17/0312 page 4
Mechanical resistance, Pull-through resistance under shear load	Please refer to ETA-17/0312 page 5
Mechanical resistance, Bending strength	Please refer to ETA-17/0312 page 5
Resistance to horizontal point loads	NPD*
Impact resistance	NPD*
Resistance to seismic actions	NPD*
Sustainable use of natural resources (BR/)	NPD*

\* No performance determined